

SinoSyn® PAO100

Polyalphaolefin(PAO)

Product Description

SinoSyn® PAO100 is a fully synthesized hydrogenated hydrocarbon base fluid produced from C10 linear alphaolefin feed stocks. It can be used as a base oil or VI-improvement for a wide range of automobile and industrial lubricant products, both mineral oil and synthetic based.

Features and Benefits

- ★ High viscosity index and excellent lubricity
- ★ High flash point and low volatility
- ★ Compatible with mineral oils and esters
- ★ Excellent oxidant resistance
- ★ Excellent shear stability and hydrolysis
- ★ Extend drain and improved fuel economy

Typical Properties

| Item | SinoSyn® PAO100 | Test Methods |
|--|-----------------|--------------|
| Appearance | Bright & Clear | Visual |
| Density@15.6 °C, g/cm ³ | 0.853 | ASTM D1298 |
| Kinematic Viscosity, mm ² /s 100 °C 40 °C | 100.8 1258 | ASTM D445 |
| Viscosity Index | 170 | ASTM D2270 |
| Flash Point COC, °C | 300 | ASTM D92 |
| Pour Point, °C | -33 | ASTM D97 |
| ASTM Color | <0.5 | ASTM D1500 |
| Acid Number, mgKOH/g | 0.01 | ASTM D974 |
| Water Content, ppm | 30 | ASTM D6304 |
| Noack Volatility Loss, wt% | 0.6 | ASTM D5800 |

Application

- ★ Gear Oils (Automotive & Industrial)
- ★ Transmission Fluids
- ★ Engine Crankcase
- ★ Greases

Additional Information

Technical White Mineral Oil, 21 CFR 178.3620(b)

National Sanitation Foundation(NSF) White book, category code H1,HX-1,Lubricants with incidental food contact.

SinoSyn® is registered trademark of NACO Synthetics.

[Http://www.nacosynthetics.com](http://www.nacosynthetics.com)

Typical properties: these are not to be construed as specifications.
2013 NACO Lubrication Co., Ltd. All right reserved.